

COLOR RESTORER

Colorless, penetrating impregnating oil that restores the original color and shine to faded surfaces. It is easy to apply and revitalizes dull surfaces. It penetrates the surface without forming a film and is highly resistant to weather conditions.

USES

Ideal for surfaces such as:

- Metal
- Plastic
- Wood
- Stone

FEATURES

- Restores the original color
- Does not create a film
- Resistant to weather conditions



TECHNICAL FEATURES

Appearance
Shade
Viscosity
Density
Surface drying
Recoat time (*)
Coverage
Dilution

Low-viscosity liquid

Transparent

30–50 sec at 23°C

0.84 ± 0,02 gr/cm³

2-3 hr

4-6hr

14–18 m²/Lt per coat

Ready to use



SURFACE PREPARATION

- Apply on dry, clean surfaces, free from any substances that may prevent penetration.
- Stir well before use.

APPLICATION

- Apply COLOR RESTORER in one coat using a brush or sponge without dilution.
- Any excess material should be removed 10–20 minutes after application with a dry cloth.

APPLICATION TOOLS

- Brush
- Sponge

TOOL CLEANING

Remove as much product as possible from tools back into the container and clean with water.

STORAGE

One year in a sealed container at storage temperatures between 5°C and 35°C

RESTRACTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply at relative humidity above 80%.
- Wet surfaces must be allowed to dry thoroughly before application.