

# PARQUET AQUA PRIMER

Water-based acrylic primer for wooden floors. It has strong adhesion and is suitable for the preparation and filling of wooden surfaces prior to the application of PARQUET AQUA. Diluted with water.

## USES

Ideal for surfaces made of:

- Wooden floors

## CHARACTERISTICS

- High gloss
- Long-lasting durability
- Easy to sand
- High coverage
- Easy application
- Strong adhesion



## TECHNICAL CHARACTERISTICS

Appearance	Low-viscosity liquid
Shade	Transparent
Viscosity	100 - 300 mPa·s at 23oC
Density	1.03 0,02 gr/cm3
Surface drying	1-2hr
Recoating time (*)	4-6hr
Coverage	8-10m2/lt per coat
Dilution	5% with water



(\*) The exact time depends on the temperature and relative humidity during application and drying.

## SURFACE PREPARATION

- Applied on dry, clean surfaces free from materials that prevent adhesion.
- The success of the application depends on proper substrate preparation and correct application of the material.

## APPLICATION

Prime with PARQUET AQUA PRIMER in two coats. Lightly sand with sandpaper. Apply PARQUET AQUA varnish in one or two coats. To adjust viscosity, it may be diluted with water up to 5%. The second coat should be applied after the first has dried.

## APPLICATION TOOLS

- Brush
- Roller

## TOOL CLEANING

During work, keep tools "wet" in the container or paint tray. Drain excess paint from the tools back into the can and clean them with water.

## STORAGE

One year in a closed container at storage temperatures between 5°C – 35°C.

## LIMITATIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when relative humidity exceeds 80%
- Wet surfaces should be allowed to dry thoroughly before application

## VOC CATEGORY

Product category A/θ (WB) "Special one-component coatings" of European Directive 2004/42/EC. VOC limit value for this category: 140 gr/lt. Maximum VOC content of the ready-to-use product: 139 gr/lt.