

PARQUET AQUA VARNISH

Water-based acrylic varnish for wooden floors. Provides a smooth, glossy, transparent surface with excellent aesthetic results, protecting the floor from abrasion, scratching, water, and detergents. Diluted with water.

USES

Ideal for surfaces made of:

- Wooden floors

CHARACTERISTICS

- High gloss
- Long-lasting durability
- Excellent finish
- High coverage
- Easy application
- Resistance to abrasion and mechanical stress
- Resistance to household detergents



TECHNICAL CHARACTERISTICS

Appearance
Shade
Viscosity
Density
Surface drying
Recoating time (*)
Coverage
Dilution

Low-viscosity liquid
Transparent
200 - 500 mPa•s at 23oC
1.03 0,02 gr/cm3
1-2hr
4-8hr
10-12m ² /lt per coat
5% with water



(*) The exact time depends on the temperature and relative humidity during application and drying.

SURFACE PREPARATION

- Applied on dry, clean surfaces free from materials that prevent adhesion.
- The success of the application depends on proper substrate preparation and correct application of the material.

APPLICATION

Prime with PARQUET AQUA PRIMER in two coats. Lightly sand with sandpaper. Apply PARQUET AQUA varnish in one or two coats. To adjust viscosity, it may be diluted with water up to 5%. The second coat should be applied after the first has dried.

APPLICATION TOOLS

- Brush
- Roller

TOOL CLEANING

During work, keep tools "wet" in the container or paint tray. Drain excess paint from the tools back into the can and clean them with water.

STORAGE

One year in a closed container at storage temperatures between 5°C – 35°C.

LIMITATIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when relative humidity exceeds 80%
- Wet surfaces should be allowed to dry thoroughly before application

VOC CATEGORY

Product category A/θ (WB) "Special one-component coatings" of European Directive 2004/42/EC. VOC limit value for this category: 140 gr/lt. Maximum VOC content of the ready-to-use product: 139 gr/lt.