

# PRESTIGE AQUA WATER RIPOLINE

High quality odorless acrylic water based enamel for wooden surfaces, ideal for indoor and outdoor use. It has excellent adhesion and is suitable for repainting of old enamel paints. It has excellent whiteness.

## USES

Ideal for:

- Metal
- Wood
- Plastic
- Wall

## FEATURES

- Very good adhesion
- Perfect Coverage
- Resistance to UV Radiation
- High Yield
- Easy to Apply



## TECHNICAL FEATURES

Shade
Viscosity
Density
pH
Gloss 60°
Surface Drying
Recoating Time
Yield
Dilution

White, Various Shades  
4000 - 6000 mPa•s at 23°C  
1.26 ± 0.02 gr/cm<sup>3</sup>  
8-9  
75  
1-2 hr  
5-8 hrs  
9-13 m<sup>2</sup>/lt per coating  
5-8% with water



## SURFACE PREPARATION

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- The success of the application depends on the correct preparation of the substrate and the correct application of the material.
- Wooden surfaces are primed with VELATURA AQUA water velvet and metal surfaces with ANTIRUST.

## APPLICATION

- The PRESTIGE AQUA WATER RIPOLINE is applied in two layers.
- For adjusting the fluidity it can be diluted by adding 5-8% water.
- The second coat should be applied after the first coat has dried.
- Wooden surfaces are primed with needlepoint. VELATURA AQUA and metallic ones with ANTIRUST.

## TOOLS CLEANING

During the work keep the tools "wet" in the paint container or tub. Drain the paint thoroughly from the tools back into the can and clean them with water.

## STORAGE

One year in a closed container and storage temperatures between 5 oC -35 oC.

## RESTRICTIONS

- Do not apply at temperatures below 5oC or above 35oC
- Do not apply when the relative humidity exceeds 80 %.
- Wet surfaces should be allowed to dry thoroughly before application.

## PDO CATEGORY

Product category A/D (S) 'Interior/exterior decoration and cladding of wood and metal' of European Directive 2004/42/EC. VOC class limit value: 130 gr/lt. Maximum VOC content of the ready-to-use product is 129 gr/lt. Contains a biocidal product: Contains C(M)IT/MIT (3:1) and 1,2-benzisothiazole-3(2H)-one. May cause an allergic reaction. Safety data sheet is available on request.