

RELIEF ACRYLIC

Water soluble coating for exterior building surfaces.
It gives an embossed surface of excellent aesthetic result.

USAGE

Ideal for surfaces of:

- Concrete
- Plasterboard
- Plaster
- Bricks
- Wood

FEATURES

- High whiteness
- Strong embossing
- Weather resistant
- High yield
- High workability



TECHNICAL FEATURES

Shades	White
Viscosity	2500 - 3000 mPa•s at 23°C
Density	1.85 ± 0,02 gr/cm ³
Ideal Temperature	15-25°C
Surface Drying	20-30min
Recoating Time	3-4hr
Deep Drying	48hr
Yield	1-1.5 kg/m ² per coating
Dilution	5-10% with water



SURFACE PREPARATION

- It is applied on dry surfaces free of materials that prevent adhesion.
- The success of the application depends on the correct preparation of the substrate with Desmo Seal solvent primer and the correct application of the material.
- The surface is cleaned of foreign particles, dust and debris.
- The surface is primed.

APPLICATION

- Relief is applied in one layer with an ordinary roller
- Then, before it dries, it is applied with a special roller to create the desired relief surface.
- If a detailed embossed surface is desired, dilute with 5-10% water.
- After drying it can be painted with any SUPERLUX acrylic paint

TOOLS CLEANING

During work, keep the tools "wet" in the paint container or tub.
Drain the paint thoroughly from the tools back into the can and clean them with water.

STORAGE

One year in a closed container and temperatures between 5°C - 35°C

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the relative humidity is above 80%.
- Wet surfaces should be allowed to dry thoroughly before application.
- The freshly painted surface should be protected from cold and moisture for at least 24 hours.

PDO CATEGORY

- Product category A/C (SB) 'Exterior walls of mineral substrate' of the European Directive 2004/42/EC.VOC class limit value : 40 gr/lit. Maximum VOC content of the ready-to-use product is 39 gr/lit.