



GENERAL CHARACTERISTICS

Plastic paint of excellent quality with high opacity and great whiteness for perfect results with easy application. Ideal for indoor use where frequent painting and touch-ups are required. Applicable on surfaces made of plaster, concrete, exposed concrete, sputtered surfaces etc. Thanks to its special composition protects the user and the environment during application. It does not contain hazardous substances, heavy metals, formaldehyde, ammonia and aromatic hydrocarbons.

CHARACTERISTICS

- High whiteness and coverage
- Resistance to watershed
- High Yield
- Easy to apply evenly
- Practically odourless and user-friendly

USES

Ideal for surfaces of:

- Concrete
- Plasterboard
- Plaster
- Bricks
- Wood

TOOLS CLEANING

During the work keep the tools "wet" in the container or in the paint tub. Drain the paint thoroughly from the tools back into the can and clean them with water.

STORAGE

One year in a closed container and storage temperatures between 5°C to 35°C.

TECHNICAL CHARACTERISTICS

Appearance:	Viscous Liquid
Shade:	White
Viscosity:	7500 - 8000 mPa·s at 23°C
Density:	1.50 ± 0,02 gr/cm ³
pH:	8-9
Surface Drying:	30-45 min
Recoating Time (*):	3-4 hr
Yield:	10-12 m ² /lt per coating
Dilution:	5-10% with water

(*): The exact time depends on the temperature and the relative humidity prevailing during the application and the drying.

SURFACE PREPARATION

- Apply to dry, clean surfaces free of materials that are not contaminated, which prevent adhesion.
- The success of the application depends on the correct preparation of the preparation of the substrate and the correct application of the material.
- The surface is primed with ACRYL BOND or DESMO SEAL Water.

APPLICATION

- When the primer starts to dry, apply the PLASTIC DECO PLAST in two layers.
- To adjust the fluidity it can be diluted by adding 5-10% water.
- The second coat should be applied after the first is dry.

LIMITATIONS

- Do not apply at temperatures below 5oC or above 35oC
- Do not apply when relative humidity exceeds 80%
- Wet surfaces should be allowed to dry thoroughly before application

PRECAUTIONS

CONTAINS a biocidal product: Contains C(M)IT/MIT (3:1) and BIT. May cause an allergic reaction. Safety data sheet provided on request.

PDO CATEGORY

Product category No (Y) Interior wall and ceiling matting (Gloss ≤25@60o) of European Directive 2004/42/EC. Limit value VOC class limit value: 30 gr/lt. Maximum VOC content of the ready-to-use product is 29gr/lt.