



TECHNICAL CHARACTERISTICS

Hue	Transparent
Viscosity	50-150 mPaes at 23°C
Density	1.01 ± 0,02 gr/cm ³
pH:	8 - 9
Surface drying	30min
Recoating time (*)	3hr
Performance	16-18 m ² /lt per coat
Dilution	50-100% with water

(*) The exact time depends on the temperature and relative humidity prevailing during application and drying.

GENERAL CHARACTERISTICS

DESMO SEAL is a Water-soluble primer for the interior and exterior building surfaces. It increases the adhesion of the final paint to the surface and improves its coverage. Practically odorless, it penetrates and stabilizes the surface.

CHARACTERISTICS

- High adhesion
- Improves the coverage of the final color
- High efficiency

USES

Ideal for surfaces of:

- Concrete
- Drywall
- Plaster
- Bricks

TOOLS CLEANING

While working, keep the tools wet in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when the air relative humidity is higher than 80%
- Wet surfaces should be allowed to dry thoroughly before application.

SURFACE PREPARATION

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- Application's success depends on the proper preparation of the surface and the correct application of the material.
- Clean the surface from foreign particles, dusts and residues.

APPLICATION

- Apply DESMO SEAL WATER SOLUBLE PRIMER on the surface
- When the primer begins to dry, the final coating is applied according to its specifications.
- To adjust fluidity it can be diluted with the addition of water of 5-100%.

STORAGE

One year in closed container, at temperatures between 5°C - 35 °C.

VOC CATEGORY

Product Category: A/h (WB) 'Binding primers' of 2004/42/EC. Maximum limit VOC value of category: 30gr/lt. Maximum VOC concentration of ready to use product: 29gr/lt.