

EASY STONE

Transparent, non-toxic acrylic-based binding resin for decorative stones and gravel. Holds loose gravel and decorative stones exactly where they are placed, while allowing water to drain. Creates an almost invisible bond on pathways, borders, flower beds, and any decorative stone area to prevent movement from wind or rain. Ready to use and easy to apply. Does not yellow due to exposure to sunlight.

USES

Ideal for surfaces such as:

- Stone
- Gravel

FEATURES

- High gloss
- Long-lasting durability
- UV resistance



TECHNICAL FEATURES

Shade:	Transparent
Viscosity:	200–500 mPa*s at 23°C
Density:	1.07 ± 0.02 g/cm ³
Surface drying time:	1–2 hr
Recoat time (*):	12–36 hr
Coverage:	6–8 m ² /L per coat
Dilution:	Ready to use



4LT/ 700ML

(*) The exact time depends on the temperature and relative humidity prevailing during application and drying.

SURFACE PREPARATION

- Apply on dry, clean surfaces free from materials that prevent adhesion.
- The success of the application depends on proper substrate preparation and correct application of the material.

APPLICATION

- Apply **EASY STONE** in two or three coats.
- Apply the first coat on a clean and dry surface, spraying slowly to ensure uniform coverage.
- Move any loose stones or gravel with a rake.
- Apply the second coat of **EASY STONE**. Once uniform coverage is achieved, press the surface to ensure better adhesion.
- After 12–36 hours, apply a third coat to the surface.

CLEANING TOOLS

During application, keep the tools “wet” inside the container. Drain the product thoroughly from the tools back into the can and clean them with water.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when relative humidity is above 80%.
- Wet surfaces must be allowed to dry thoroughly before application.

STORAGE

One year in a closed container at storage temperatures between 5°C and 35°C.

VOC CATEGORY

Product category A/h (Y) “Primer coatings” according to European Directive 2004/42/EC. Category limit value for VOC: 30gr/Lt. Maximum VOC content of the ready-to-use product: 29gr/Lt.