



## TECHNICAL CHARACTERISTICS

Shade	Colorless
Viscosity	50-150 mPa·s at 23°C
Density	1.01 ± 0,02 gr/cm <sup>3</sup>
pH:	8 - 9
Surface drying	30min
Recoating time (*)	3hr
Yield	16-18 m <sup>2</sup> /lt per coat
Dilution	Ready to use

(\*) The exact time depends on the temperature and relative humidity prevailing during application and drying.

## GENERAL CHARACTERISTICS

HY - PRIMO is a Water-soluble hybrid primer for external and internal building surfaces. It increases the adhesion of the final paint to the surface and improves its coverage. Practically odorless, it impregnates and stabilizes the surface.

## CHARACTERISTICS

- High adhesion
- Hybrid technology
- Resistance to weather conditions
- High efficiency

## USES

Ideal for surfaces of:

- Concrete
- Drywall
- Plaster
- Bricks

## TOOLS CLEANING

While working, keep the tools wet in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with water.

## RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when the air relative humidity is higher than 80%
- Wet surfaces should be allowed to dry thoroughly before application.
- The freshly painted surface should be protected from cold and moisture for at least 24hr.

## SURFACE PREPARATION

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- Application's success depends on the proper preparation of the surface and the correct application of the material.
- Clean the surface from foreign particles, dusts and residues.

## APPLICATION

- Apply HY-PRIMO on the surface in one coat
- When the primer starts to dry, the final paint is applied according to its specifications

## STORAGE

One year in closed container, at temperatures between 5°C - 35 °C.

## VOC CATEGORY

Product Category: A/h (WB) 'Binding primers' of 2004/42/EC. Maximum limit VOC value of category: 30gr/lt. Maximum VOC concentration of ready to use product: 29gr/lt.